

Ordering Information

Example: KR1DOR10-TRM < r > sr'ii

| Product | Power | Replacement | Color Temperature | lm | Beam Spread | Beam Angle | Beam Diameter |
|--------------|-------|-------------|-------------------|--------|-------------|------------|---------------|
| KR1DOR10-TRM | 10W | 10W | 3000K | 1000lm | 25° | 1.5m | 1.5m |
| KR1DOR10-TRM | 10W | 10W | 4000K | 1000lm | 25° | 1.5m | 1.5m |
| KR1DOR10-TRM | 10W | 10W | 5000K | 1000lm | 25° | 1.5m | 1.5m |
| KR1DOR10-TRM | 10W | 10W | 3000K | 1000lm | 30° | 1.8m | 1.8m |
| KR1DOR10-TRM | 10W | 10W | 4000K | 1000lm | 30° | 1.8m | 1.8m |
| KR1DOR10-TRM | 10W | 10W | 5000K | 1000lm | 30° | 1.8m | 1.8m |

Projected LED Lumen Maintenance

| Operating hours | 0 | 25000 | 50000 |
|-----------------|---|-------|-------|
| Lumen | 1 | 0.91 | 0.8 |

Data references the extrapolated performance projections for the SHOEBOX LED platform in a 25°C ambient, based on 10,000 hours of LED testing (tested per IESNA LM-80-08 and projected per IESNA TM-21-11).

Dimensions

After-sale Service

Please use licensed electrical contractor for installation. Please contact OPTIK LED for warranty details.

NOTE: Actual performance may differ as a result of end-user environment and application. All values are without notice.