


Ordering Information

Example: OP-CH-100W-40K-N-G


Product	Power	Replacement	Color Temperature	Photocell	Furnish	Head connector
OP-CH-100W	100W 1 module	175-200W MH/HPS	40K 4000K 50K 5000K	N not photocell Y yes photocell	G-Gray	
OP-CH-120W	120W 1 module	200-250W MH/HPS				
OP-CH-150W	150W 1 module	250-400W MH/HPS				
OP-CH-200W	200W 1 module	400-450W MH/HPS				
OP-CH-240W	240W 1 module	600-750W MH/HPS				
OP-CH-300W	300W 1 module	1000W MH/HPS				

Connector options: Slip titter


Photo-metrics: IES files Available




Type II



Type III



Type IV



Type V

Projected LED Lumen Maintenance

Operating hours	0	25000	50000
Lumen	1	0.91	0.8

Data references the extrapolated performance projections for the SHOEBOX LED platform in a 25°C ambient, based on 10,000 hours of LED testing (tested per IESNA LM-80-08 and projected per IESNA TM-21-11).

After-sale Service

Please use licensed electrical contractor for installation. Please contact OPTIK LED for warranty details.

NOTE: Actual performance may differ as a result of end-user environment and application. All values are without notice.